

# WYRESTORM EXPRESS™ 1X4 HDMI 4K SPLITTER

EXP-SP-0104-4K



## KEY FEATURES:

- Fully 4K compatible - 3840 (UHD) and 4096 (DCI) 2160 @ 30Hz with 4K color palette 4:2:2
- Plug and Play connectivity - automatic EDID and HDCP device communication
- Low profile 18mm/0.7 for greater installation convenience
- Create combined 4K/HD distributions with additional WyreStorm inline scaler (sold separately)


Ultra Slim, Ultra High Definition. The WyreStorm Express EXP-SP-0104-4K 1x4 4K Splitter enables lossless duplication and distribution of a single HDMI 4K or HD source to up to 4 connected outputs for simple, flexible and reliable content replication to multiple display devices supporting resolutions up to 4Kx2K.

## ADDITIONAL FEATURES & BENEFITS:

- Supports 4K resolutions up to 4096x2160@30Hz and HD resolutions up to 1080p @ 60Hz
- 4K color @ 24bit with 4K chroma subsampling color palette 4:2:2, 1080p @ 36bit
- Transmission distances up to 10m/33ft (4K/1080p input, 4K output), 15m/49ft (1080p output) using standard HDMI cables
- Multichannel audio supported (mirrors source)
- Threaded power port for locking or standard 5v DC connection
- Full 3D compatibility up to 1080p - frame packing/ sequential (Blu-ray) and interlaced stereoscopic (satellite/ cable broadcasts)
- Front panel LED indication for I/O and Power connectivity
- Slimline chassis for space-saving local installation
- Supports HDMI 1.4a and HDCP
- Units cascadable to create larger systems
- Easily create cost effective, scalable combined 4K/HD distributions by connecting WyreStorm EXP-SCL-DAC-4K scaler with Dolby downmixer (sold separately)

## IN THE BOX

- 1 x EXP-SP-0104-4K WyreStorm Express™ 1x4 HDMI 4K Splitter
- 1 x Quickstart guide (Quickstart and full manual downloadable from [wyrestorm.com](http://wyrestorm.com))
- 1 x 5v DC 1A power adapter
- 2 x Mounting brackets



**NOTE: Maximum HDMI transmission distance**  
Input - 10m/33ft (4K & 1080p)  
Output - 10m/33ft (4K), 15m/49ft (1080p)




US OFFICE:  
TEL: +1 901 384 3575  
FAX: +1 901 384 3574

EMEA OFFICE:  
TEL: + 44 (0) 1793 230 343  
FAX: + 44 (0) 1793 230 583

## SPECIFICATIONS

Input	1 x HDMI INPUT (Type A female connector)
Output	4 x HDMI OUTPUT (Type A female connector)
Input/Output Signal Type	HDMI 1.4a, 3D, DVI 1.0
Input/Output Resolution Support	480i, 480p, 576i, 576p, 720p, 1080i, 1920x1080p @60Hz, 3840 (UHD), 4096 (DCI) 2160 @30Hz
Color	4K color @ 24bit with 4K chroma subsampling color palette 4:2:2, 1080p @ 36bit
Maximum Data Rate	10.2 Gpbs
Maximum Pixel Clock	340 MHz
Input Video Signal	0.5~1.2 V p-p
Input DDC Signal	5V
Video Impedance	100Ω
Power Supply	5V DC 1A
Power Consumption	1080p: 1.2 W (Max.), 4K: 1.7 W (Max.)
Operating Temperature	32°F ~ 95°F (0°C ~ 35°C), 10% ~ 90%, non-condensing
Storage Temperature	-4°F ~ 140°F (-20°C ~ 70°C), 10% ~ 90%, non-condensing
ESD Protection	±4 kV (Contact discharge) , ±8 kV (Air discharge)
Product Dimension (WxHxD)	140mm/5.5" x 18mm/0.7" x 65mm/2.6"
Product Weight	0.26 kg
Certification	CE, FCC, RoHS



For product installation assistance and troubleshooting, find additional WyreStorm Express product information at [wyrestorm.com](http://wyrestorm.com)

For technical support contact: US: +1 901 384 3575 EMEA: +44 (0) 1793 230 343 EMAIL: [support@wyrestorm.com](mailto:support@wyrestorm.com)